

# MASONS / E2 REDWAY FLASHING SOLUTIONS WARRANTY



**MASONS**  
Designed Smart, Built Tough.

V2.0 February 2024

## WARRANTY GENERAL TERMS

**Limited Warranty:** Masons NZ Limited warrants for a period of 15 years to the original consumer purchaser from the date of purchase that Cavity Closers, Internal Flashings, Sill Tray System and Concrete Crack Inducers (the “Products”) will be free from defects in materials and workmanship, subject to the conditions set forth in this limited warranty, under normal use and service, and when properly specified and installed.

Durability is expected to be a minimum of 15 Years or the serviceability life of the cladding or joinery.

Crack inducer has an expected 50 year durability.

Liability is limited to replacement of products proven to be defective. In no event shall Masons be liable for any incidental or consequential damages.

### Conditions of Warranty:

It shall be the sole responsibility of the user to determine the suitability of the Masons Product and material for each intended use, and the user assumes all risks and liability in connection with the use or inability to use the product.

This Limited Warranty is void should any damages or defects result from or are in any way attributable to:

- › Improper storage and handling of the Product
- › Improper installation of the Product
- › If the Product has been altered or modified
- › Where Products are designed to work together as a system, Masons NZ Ltd products are not warranted if installed in conjunction with other non-Masons NZ Ltd products
- › Accepted cladding installation methods have not been followed
- › The project/building was not designed or constructed in strict compliance with the standards set forth in the New Zealand Building Code
- › Products are subjected to excessive UV exposure before or after installation

- › Natural disasters, including but not limited to, earthquakes, floods, cyclones, or other natural phenomena

### Product Information

The uPVC compound used to manufacture Masons Redway E2 back flashings is industry-standard, durable, rigid, chemically resistant and designed for outdoor weathertightness. As per the NZBC E2/AS1 Table 20 and Section 4.3.1, uPVC is a suitable material for Claddings and Flashings that are hidden from direct UV exposure and when the chemical composition fulfills the requirement of AS/NZS 4256 Part 2.

Redway E2 flashings have a BRANZ appraisal uPVC is also an inherently fire resistant material that will not spread flames. It is self-extinguishing once the flame source has been removed

- › The warranty does not cover failure arising from the failure to follow all of Masons NZ Ltd advice.
- › Normal wear and tear are excluded from this warranty.

All relevant information is available from Masons NZ Ltd (refer to [www.mpb.co.nz](http://www.mpb.co.nz)).