

Flexible Ducts

Aluminium



MASONS
Designed Smart, Built Tough.



Back Draft Shutter

REGULATES AIR FLOW

In Air Ducts

SPRING-LOADED

For Positive Closure

DIRECTIONAL AIR FLOW

One-way Design



Flexible Aluminium Duct

This self-supporting duct can be bent to send airflow in your desired direction without creating sharp bends that restricts airflow.

CONSTITUTION

2x Aluminium Layers

TEMPERATURE RANGE

-30 °C to 150 °C

OPERATION PRESSURE

3000 Pa

Description	Vent Size (mm)	Masons Code
Vent Back Draft Damper 100	100	VENTBDD100
Vent Back Draft Damper 125	125m	VENTBDD125
Vent Back Draft Damper 150	100m	VENTBDD150

Description	Vent Size (mm)	Masons Code
Flexible Aluminium Duct 100mm 1m boxed	100	VENTIFXAL100MMX1M
Flexible Aluminium Duct 100mm 3m boxed	100	VENTIFXAL100MMX3M
Flexible Aluminium Duct 100mm 6m boxed	100	VENTIFXAL100MMX6M
Flexible Aluminium Duct 125mm 1m boxed	125	VENTIFXAL125MMX1M
Flexible Aluminium Duct 125mm 3m boxed	125	VENTIFXAL125MMX3M
Flexible Aluminium Duct 125mm 6m boxed	125	VENTIFXAL125MMX6M
Flexible Aluminium Duct 150mm 1m boxed	150	VENTIFXAL150MMX1M
Flexible Aluminium Duct 150mm 3m boxed	150	VENTIFXAL150MMX3M
Flexible Aluminium Duct 150mm 6m boxed	150	VENTIFXAL150MMX6M
Flexible Aluminium Duct 200mm 3m boxed	200	VENTIFXAL200MMX3M